DRY PTFE SPRAY

Multi purpose, food grade PTFE spray for light lubrication.
Non-toxic PTFE spray for use as a dry anti-stick film or light lubrication of links, pins, chutes, slides etc. operating in food/clean environments.

FEATURES

- Temperature range –200^{0}C to 270^{0}C
- Light film – does not easily transfer
- Effective anti-stick properties
- Insoluble in water and solvents
- Clean, dry, non-toxic, colourless film
- Does not contain: mineral hydrocarbons, animal derived materials, nut oils or genetically modified ingredients.
- FDA Group 21 CFR 178.3570
- NSF H1 registered – 123703
- DIN V 10517

DIRECTIONS FOR USE

- Shake well, hold upright and spray from a distance of 15-25 cms
- Ensure adequate ventilation
- Do not smoke during use. Wash hands thoroughly before smoking or handling tobacco products

Technical and Safety Data Sheets are available from:

Fax Back Facility : +44 (0)113 232 2770
Web Site : www.rocol.com
Customer Service : +44 (0)113 232 2700

TECHNICAL DATA

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760
www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.
ROCOL is a trade mark of ITW Inc.
The information in this publication is based on our experience and reports from customers.
There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

DRY PTFE SPRAY

TECHNICAL DATA (typical values)

Appearance (applied film)	Colourless, dry film
Base type	PTFE
Propellant	Hydrocarbon
Solvent	Blend of hydrocarbon and alcohol
Temperature range	-200^{0}C to 270^{0}C
Storage	Storage temperature should be kept below 50 °C. Storage area should be: out of direct sunlight.
Pack sizes	400 ml

TECHNICAL DATA

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.
ROCOL is a trade mark of ITW Inc.
The information in this publication is based on our experience and reports from customers.
There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.