



FOODLUBE CHAIN SPRAY

Food grade multipurpose chain and conveyor lubricant in an aerosol. Non-toxic, water resistant lubricant designed for the effective lubrication of all types of chains & conveyors operating in food/clean environments.

FEATURES

- Ø Temperature range –20°C to 150°C
- Ø Highly resistant to water wash off
- Ø Non-drip tenacious film
- Ø Excellent penetration
- Ø Good load carrying capabilities
- Ø Excellent corrosion protection
- Ø Does not contain: mineral hydrocarbons, animal derived materials, nut oils or genetically modified ingredients.
- Ø FDA Group 21 CFR 178.3570
- Ø NSF H1 registered – 122878
- Ø DIN V 10517

DIRECTIONS FOR USE

- Ø Shake well before use and spray from a distance of 15-25 cm.

Technical and Safety Data Sheets are available from:

Fax Back Facility : +44 (0)113 232 2770
Web Site : www.rocol.com
Customer Service : +44 (0)113 232 2700

Issue 15610d: Jan-04

1

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

TECHNICAL DATA



FOODLUBE CHAIN SPRAY

TECHNICAL DATA (typical values)

Appearance	Pale yellow, almost colourless liquid
Base type	Polyalphaolefin
Propellant	Hydrocarbon
Temperature range	-20 ⁰ C to 150 ⁰ C
Base fluid viscosity at 40 ⁰ C	150 cSt
Shell 4 ball (IP 239)(ASTM D2596)	
Weld load	180 kg
Storage	Storage temperature should be kept below 50 °C. Storage area should be: out of direct sunlight.
Pack sizes	400 ml

Issue 15610d: Jan-04

2

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.ocol.com

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

TECHNICAL DATA