



# FOODLUBE EXTREME

**Food grade multipurpose EP grease.  
Non-toxic lubricant designed for the effective lubrication and protection  
of ball, roller and plain bearings operating in food/clean environments.**

## FEATURES

- Ø Temperature range –30°C to 160°C
- Ø Excellent EP performance (355kg weld load)
- Ø Highly resistant to water wash off
- Ø Excellent corrosion protection
- Ø Does not contain: mineral hydrocarbons, animal derived materials, nut oils or genetically modified ingredients.
- Ø FDA Group 21 CFR 178.3570
- Ø NSF H1 registered – 132235
- Ø DIN V 10517

## DIRECTIONS FOR USE

- Ø Apply manually or with a suitable applicator e.g. ROCOL grease gun.
- Ø The previous lubricant should be removed prior to application.

### Technical and Safety Data Sheets are available from:

**Fax Back Facility** : +44 (0)113 232 2770  
**Web Site** : [www.rocol.com](http://www.rocol.com)  
**Customer Service** : +44 (0)113 232 2700

Issue 15241a: Dec-03

1

### **ROCOL Lubricants**

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

[www.rocol.com](http://www.rocol.com)

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers.  
There are many factors outside our control or knowledge which affect the use and performance  
of our products, for which reason it is given without responsibility.

TECHNICAL DATA



# FOODLUBE EXTREME

## TECHNICAL DATA (typical values)

Appearance	Beige, tenacious grease
NLGI No. (IP 50)(ASTM D217)	NLGI No. 2
Base type	Synthetic
Thickener	Organo Clay
Solids	High Load White Solids
Temperature range	-30°C to 160°C
Drop point	None
Base fluid viscosity at 40°C	150 cSt
Shell 4 ball (IP 239)(ASTM D2596)	
Weld load	355 kg
EMCOR Corrosion Test (IP220)	0 Rating
Copper corrosion test (IP 112)(ASTM D130)	Pass
Water washout test (IP 215)(ASTM D 1264)	<2.0%
Storage	Storage temperature should be controlled to between 1 and 40°C.

Issue 15241a: Dec-03

2

### **ROCOL Lubricants**

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

[www.rocol.com](http://www.rocol.com)

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

TECHNICAL DATA