



FOODLUBE HI-POWER

**Food grade, synthetic, hydraulic, compressor and airline fluids.
Also suitable for low temperature applications particularly chains and gearboxes operating in food/clean environments.**

Viscosity grades: ISO VG 22, 32, 46, 68, 100

FEATURES

- Ø General temperature range -20°C to 100°C
- Ø Can be used down to -50°C depending on viscosity grade and application.
- Ø L-CO; unique low carry over system to enhance compressor performance
- Ø High thermal stability
- Ø Does not form deposits, sludge or varnish
- Ø Low foaming
- Ø Do not contain: mineral hydrocarbons, animal derived materials, nut oils or genetically modified ingredients.
- Ø FDA Group 21 CFR 178.3570
- Ø NSF H1 registered
 - Foodlube Hi-Power 22 - 122180
 - Foodlube Hi-Power 32 - 122181
 - Foodlube Hi-Power 46 - 122182
 - Foodlube Hi-Power 68 - 122183
 - Foodlube Hi-Power 100 - 122184
- Ø DIN V 10517

DIRECTIONS FOR USE

- Ø For optimum performance drain & flush prior to filling with ROCOL.

Technical and Safety Data Sheets are available from:

Fax Back Facility : +44 (0)113 232 2770
Web Site : www.rocol.com
Customer Service : +44 (0)113 232 2700

Issue 15796c: Jan-04

1

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers.
There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.



FOODLUBE HI-POWER

TECHNICAL DATA (typical values)

Appearance	Clear liquid
Base type	Polyalphaolefin
viscosities at 40 ⁰ C	
Foodlube Hi-Power 22	22 cSt
Foodlube Hi-Power 32	32 cSt
Foodlube Hi-Power 46	46 cSt
Foodlube Hi-Power 68	68 cSt
Foodlube Hi-Power 100	100 cSt
General temperature range	-20 ⁰ C to 100 ⁰ C
Meets performance requirements of:	
	Vickers M-2952-S
	Vickers I-268-S
	U.S. Steel 127
Extreme low temperatures (Contact Technical Department to discuss specific applications)	Can be used down to -50 ⁰ C depending on viscosity grade and application.
Storage	Storage temperature should be controlled to between 1 and 40 °C.
Pack sizes	5 ltr, 20 ltr, 200 ltr

TECHNICAL DATA

Issue 15796c: Jan-04

2

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.