# FOODLUBE HI-TORQUE (with SUPS)

**High performance, food grade, synthetic gearbox fluids.
Non-toxic gearbox lubricants with the unique Start Up Protection System that protects on start up as well as during use.**

***Viscosity grades: ISO VG 150, 220, 320, 460***

## FEATURES

- Ø Temperature range –20$^0$C to 150$^0$C
- Ø Outstanding EP performance (FZG load stage 12)
- Ø Highly resistant to water wash off
- Ø Increased service intervals
- Ø Excellent corrosion protection
- Ø Do not contain: mineral hydrocarbons, animal derived materials, nut oils or genetically modified ingredients.
- Ø FDA Group 21 CFR 178.3570
- Ø NSF H1 registered - Foodlube Hi-Torque 150 – 121604
  Foodlube Hi-Torque 220 – 122073
  Foodlube Hi-Torque 320 – 122072
  Foodlube Hi-Torque 460 – 121071
- Ø DIN V 10517

## DIRECTIONS FOR USE

- Ø For optimum performance drain & flush prior to filling with ROCOL.

**Technical and Safety Data Sheets are available from:**

**Fax Back Facility** : +44 (0)113 232 2770
**Web Site** : www.rocol.com
**Customer Service** : +44 (0)113 232 2700



**ROCOL Lubricants**

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.
ROCOL is a trade mark of ITW Inc.
The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

TECHNICAL DATA

# FOODLUBE HI-TORQUE (with SUPS)

TECHNICAL DATA

## TECHNICAL DATA (typical values)

| | |
|---|---|
| Appearance | Pale yellow, almost colourless, fluid |
| | |
| Base type | Polyalphaolefin |
| | |
| viscosities at $40^0$C | |
| Foodlube Hi-Torque 150 | 150 cSt |
| Foodlube Hi-Torque 220 | 220 cSt |
| Foodlube Hi-Torque 320 | 320 cSt |
| Foodlube Hi-Torque 460 | 460 cSt |
| | |
| Temperature range | $-20^0$C to $150^0$C |
| | |
| FZG load stage | 12 |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| Storage | Storage temperature should be controlled to between 1 and 40 °C. |
| | |
| Pack sizes | 5 ltr, 20 ltr, 200 ltr |
| | |



**ROCOL Lubricants**

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.
ROCOL is a trade mark of ITW Inc.
The information in this publication is based on our experience and reports from customers.
There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.