



FOODLUBE HIGH TEMP GREASE 2

Food grade, high temperature, grease fortified with PTFE.
Non-toxic lubricant designed for the effective lubrication and protection of ball, roller and plain bearings operating in food/clean environments.

FEATURES

- Ø Temperature range –20°C to 200°C
- Ø Good anti-wear performance
- Ø Highly resistant to water wash off
- Ø Suitable for slow moving bearings and slides
- Ø Ideal for use as a friction reducing lubricant
- Ø Does not contain: mineral hydrocarbons, animal derived materials, nut oils or genetically modified ingredients.
- Ø FDA Group 21 CFR 178.3570
- Ø NSF H1 registered – 122065
- Ø DIN V 10517

DIRECTIONS FOR USE

- Ø Apply manually or with an applicator suitable for silicone lubricants.
- Ø It is recommended that ROCOL Foodlube High Temp Grease 2 is not mixed with any other lubricant.

Technical and Safety Data Sheets are available from:

Fax Back Facility : +44 (0)113 232 2770
Web Site : www.rocol.com
Customer Service : +44 (0)113 232 2700

Issue 15251f: Jan-04

1

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers.
There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.



FOODLUBE HIGH TEMP GREASE 2

TECHNICAL DATA (typical values)

Appearance	White, semi-translucent grease
NLGI No. (IP 50)(ASTM D217)	NLGI No. 2
Base type	Silicone
Thickener	Silica
Solids	PTFE
Temperature range	-20 ⁰ C to 200 ⁰ C
Drop point	Non-melting
Base fluid viscosity at 40 ⁰ C	1000 cSt
Shell 4 ball (IP 239)(ASTM D2596)	
Weld load	180 kg
Load-wear index	25.5 kg
Water washout test (IP 215)(ASTM D 1264)	<2%
Storage	Storage temperature should be controlled to between 1 and 40 °C.
Pack sizes	380g cart, 4kg, 18kg

Issue 15251f: Jan-04

2

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

TECHNICAL DATA