



FOODLUBE MULTI-LUBE FLUID

Food grade multi-purpose penetrating lubricant fortified with PTFE. Non-toxic lubricating, penetrating and water displacing lubricant. Ideal for use on chains, bearings & slides in food/clean environments.

FEATURES

- Ø Available in a convenient trigger pack or bulk fluid
- Ø Temperature range -50°C to 180°C
- Ø Good load carrying properties
- Ø Good dewatering properties
- Ø Excellent penetration
- Ø Long life lubricating film with PTFE
- Ø Excellent corrosion protection
- Ø Does not contain: mineral hydrocarbons, animal derived materials, nut oils or genetically modified ingredients.
- Ø FDA Group 21 CFR 178.3570
- Ø NSF H1 registered - 127935
- Ø DIN V 10517

DIRECTIONS FOR USE

- Ø SHAKE THOROUGHLY BEFORE USE
- Ø For best results apply to a clean surface

Technical and Safety Data Sheets are available from:

Fax Back Facility : +44 (0)113 232 2770
Web Site : www.rocol.com
Customer Service : +44 (0)113 232 2700

Issue 15120c: Jan-04

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

TECHNICAL DATA



FOODLUBE MULTI-LUBE FLUID

TECHNICAL DATA (typical values)

Appearance	Light coloured liquid
Base type	Synthetic fluid
Viscosity at 40°C	17cSt
Solids	PTFE
Temperature range	-50°C to 180°C
Shell 4 ball (IP 239)(ASTM D2596)	
Scar diameter	0.43 mm (40kg for 1 hour)
Copper corrosion test (IP 112)(ASTM D130)	1b
Evaporation loss at 175°C (IP 183)(ASTM D972)	4.1%
Storage	Storage temperature should be controlled to between 1 and 40°C.
Pack sizes	500 ml, 5 ltr

Issue 15120c: Jan-04

2

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

TECHNICAL DATA