



## TECHNICAL DATA

# RTD Chlorine-Free Compound

Hand Applied Metal Cutting Lubricant

TECHNICAL DATA

### Description

ROCOL RTD Chlorine-Free Compound is a soft paste for use in reaming, tapping and drilling and other metal cutting operations. ROCOL RTD Chlorine Free Compound is suitable for all metals including hardened steels, nimonics and titanium alloys. ROCOL RTD Chlorine Free Compound has been specifically developed to satisfy ever increasing environmental and health and safety needs in today's markets.

### Outstanding Features

- Extends tool life
- Improves surface finish
- Increases removal rates
- Reduces production costs

### Directions for use

Apply directly to the tool or workpiece by brush, or by dipping tool into the compound.

### Technical Data

<i>Appearance:</i>	<i>Red Paste</i>
<i>Odour:</i>	<i>Mild Sulphur</i>
<i>Solvents:</i>	<i>None</i>
<i>Shell 4 Ball</i>	
<i>Weld Load:</i>	<i>800kg</i>
<i>Tapping Torque (316 Stainless Steel):</i>	<i>8.6 NM</i>
<i>Corrosion (Steel Plate at 175°C for 5 minutes):</i>	<i>None</i>
<i>Storage: 0° to 40°C.</i>	<i>Normal storage</i>

### ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: 0113 232 2600 Fax: 0113 232 2760

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW inc

The information in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which effect the use and performance of our products for which reason the information in this publication is given without responsibility

## Pack sizes and part codes

450g	part code	53513
4.5kg	part code	53516

## Health and Safety

Safety data sheet is available from the Customer Service Department, ROCOL Lubricants, ROCOL House, Swillington, Leeds, LS26 8BS, England.

**Telephone:** 0113 232 2700, (When calling from outside UK: 44 113 232 2700);

**Fax:** 0113 232 2760, (When faxing from outside UK: 44 113 232 2760).

Issue: RTD Chlorine Free Compound TDS 5351  
Date: Jan-04

## ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: 0113 232 2600 Fax: 0113 232 2760

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW inc

The information in this publication is based on our experience and reports from customers.  
There are many factors outside our control and knowledge which effect the use and performance of our products  
for which reason the information in this publication is given without responsibility

TECHNICAL DATA