TECHNICAL DATA

RTD Foamcut

Metal Cutting Lubricant Spray

Description

ROCOL RTD Foamcut is a metal cutting lubricant specially formulated to provide extreme pressure cutting performance in an economical to use foaming aerosol.ROCOL RTD Foamcut is suitable for all metal cutting operations on a wide range of ferrous and non ferrous metals, including copper, brass and aluminium. The foaming action ensures the lubricant rapidly penetrates to the cutting edges without running off the tool or workpiece and allows economical application, even in deep holes. This prolongs tool life and improves surface finish.

Outstanding Features

- **Extends tool life**
- **Improves surface finish**
- **Increases removal rates**
- **Reduces production costs**

Directions for use

ROCOL RTD Foamcut should be shaken well before use then sprayed directly onto the tool or workpiece from a distance of 15 - 30 cm. The direction control straw allows greater accessibility to difficult operations and enables application exactly where needed. Ensure adequate ventilation.

Technical Data (typical values)

Appearance:	*Creamy-white foam*
Odour:	*Mild*
Solvents:	*None*
Nitrites:	*None*
Silicones:	*None*
Storage:	*Storage temperature should be kept below 50°C. Storage area should be out of direct sunlight.*

TECHNICAL DATA

ROCOL Lubricants
ROCOL House, Swillington, Leeds LS26 8BS, England.
Tel: 0113 232 2600 Fax: 0113 232 2760
ROCOL is a BS EN ISO 9001 registered company.
ROCOL is a trade mark of ITW inc
The information in this publication is based on our experience and reports from customers.
There are many factors outside our control and knowledge which effect the use and performance of our products
for which reason the information in this publication is given without responsibility

Pack sizes and part codes

300ml part code 53041

Health and Safety

Safety data sheet is available from the Customer Service Department, ROCOL Lubricants, ROCOL House, Swillington, Leeds, LS26 8BS, England.
Telephone: 0113 232 2700, (When calling from outside UK: 44 113 232 2700);
Fax: 0113 232 2760, (When faxing from outside UK: 44 113 232 2760).

Issue: RTD Foamcut TDS 5304
Date: Jan-04

TECHNICAL DATA

ROCOL Lubricants
ROCOL House, Swillington, Leeds LS26 8BS, England.
Tel: 0113 232 2600 Fax: 0113 232 2760
ROCOL is a BS EN ISO 9001 registered company.
ROCOL is a trade mark of ITW inc
The information in this publication is based on our experience and reports from customers.
There are many factors outside our control and knowledge which effect the use and performance of our products
for which reason the information in this publication is given without responsibility