ANTI SEIZE SPRAY

Copper based anti seize spray for all static fasteners and mechanisms. Anti Seize Spray is an assembly and anti seize lubricant that prevents pick up and seizure even in wet, dirty and corrosive conditions.

FEATURES

- Temperature range –10^{0}C to 1100^{0}C
- Prevents pick up and seizure of static threaded fasteners
- Lubricates, protects and eases dismantling
- Effective even in the most aggressive environments
- Insoluble in water
- Ideal for furnaces, exhaust systems, dockside and oil rig applications
- Aerosol applied for convenience and economy

DIRECTIONS FOR USE

- Shake can thoroughly.
- Hold upright and spray from a distance of 15-30 cm (6-12 inches).

Technical and Safety Data Sheets are available from:

Fax Back Facility : +44 (0)113 232 2770
Web Site : www.rocol.com
Customer Service : +44 (0)113 232 2700

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760
www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.
ROCOL is a trade mark of ITW Inc.
The information in this publication is based on our experience and reports from customers.
There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

TECHNICAL DATA

ANTI SEIZE SPRAY

TECHNICAL DATA (typical values)

Appearance	Silvery copper coloured slightly greasy film
Base type	Mineral oil
Thickener	Organically modified clay
Propellant	LPG (Hydrocarbon)
Solvent	Hydrocarbon
Solids	Copper, Graphite, MoS_2 Aluminium
Solids content in applied film	Approximately 40%
Temperature range	-10^0C to 1100^0C
Water solubility of applied film	Insoluble
Storage	Storage temperature should be kept below 50 °C. Storage area should be: out of direct sunlight.
Pack sizes	400ml

TECHNICAL DATA

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.
ROCOL is a trade mark of ITW Inc.
The information in this publication is based on our experience and reports from customers.
There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.