ANTI SEIZE STAINLESS

Anti seize paste specially formulated for nimonic and stainless steel. Nickel-free paste designed specifically for nimonic, stainless and silver coated fasteners subjected to high temperatures for long periods in the Aerospace and Power Generation Industries.

FEATURES

- Temperature range –40^{0}C to 1000^{0}C
- Provides even torque loads and prevents galling and pick up on assembly
- Protects against wet conditions and chemical attack
- Excellent anti seize properties over extended periods at high temperatures
- Contains extremely low levels of chlorine and sulphur
- Formerly known as ASC251T
- Approved to MSRR 4008, Rolls Royce Plc OMAT Item 4/62

DIRECTIONS FOR USE

- Apply as a thin film by brushing or wiping onto a clean dry surface.
- For best results apply to both the male and female parts.

Technical and Safety Data Sheets are available from:

Fax Back Facility : +44 (0)113 232 2770
Web Site : www.rocol.com
Customer Service : +44 (0)113 232 2700

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760
www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.
ROCOL is a trade mark of ITW Inc.
The information in this publication is based on our experience and reports from customers.
There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

TECHNICAL DATA

ANTI SEIZE STAINLESS

TECHNICAL DATA (typical values)

Appearance	Stiff black paste
Carrier	Synthetic hydrocarbon
Solids	Graphite, Calcium Fluoride
Temperature range	-40^{0}C to 1000^{0}C
Anti seize properties	
100 hours at 1000^{0}C (A286 silver coated nut & bolt)	
Tightening torque	11.5 Nm
Break loose torque	20.2 Nm
Specifications	
Rolls Royce	MSRR 4008
	R-R OMAT 4/62
	COMAT 10-110
Naval Cat No	0475-179-9539
NATO Stock No	8030-99-179-9539
BAE Systems	For high nickel alloys
Storage	Storage temperature should be controlled to between 1 and 40 °C.
Pack sizes	500g

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.
ROCOL is a trade mark of ITW Inc.
The information in this publication is based on our experience and reports from customers.
There are many factors outside our control or knowledge which affect the use and performance
of our products, for which reason it is given without responsibility.

TECHNICAL DATA