



CHAIN & DRIVE FLUID

High performance EP chain and conveyor lubricant.
Designed to effectively penetrate, lubricate and protect against
corrosion. Ideal for use in automatic lubricators.

FEATURES

- Ø Temperature range -15°C to 120°C
- Ø Outstanding EP performance (250 kg weld load)
- Ø Excellent penetration
- Ø Tenacious water resistant film
- Ø Excellent corrosion protection
- Ø Applied film has good adhesion, reducing dripping or throw off

DIRECTIONS FOR USE

- Ø ROCOL Chain & Drive Fluid has been designed for application by automatic lubricators and should be used in accordance with the lubricator manufacturer's instructions
- Ø It can also be applied directly to the chain by brush or oilcan if desired

Technical and Safety Data Sheets are available from:

Fax Back Facility : +44 (0)113 232 2770

Web Site : www.rocol.com

Customer Service : +44 (0)113 232 2700

Issue 22306d: Jan-04

1

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers.
There are many factors outside our control or knowledge which affect the use and performance
of our products, for which reason it is given without responsibility.

TECHNICAL DATA



CHAIN & DRIVE FLUID

TECHNICAL DATA (typical values)

Appearance	Amber oily liquid
Base type	Mineral oil
Performance additives	EP
Temperature range	-15 ⁰ C to 120 ⁰ C
Pour point	-24 ⁰ C
Base fluid viscosity at 40 ⁰ C	131cSt
Base fluid viscosity at 100 ⁰ C	15 cSt
Viscosity index	118
Shell 4 ball (IP 239)(ASTM D2596)	
Weld load	250 kg
Mean hertz load	58.6 kg
Corrosion tests	
Salt Spray at 35 ⁰ C for 24 hours	No corrosion
Water Spray for 7 days	1%
Humidity, 14 days at 100% RH at 40 ⁰ C	1%
Storage	Storage area should be: out of direct sunlight. Storage temperature should be kept below 50 °C.
Pack sizes	300 ml

Issue 22306d: Jan-04

2

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

TECHNICAL DATA