



## CHAIN GUARD 280

High temperature, long life, EP chain and conveyor lubricant. Specially formulated for the lubrication of conveyor chains and bearings operating at temperatures up to 280°C. Particularly suitable for stenters, drying machines, kilns, bakery ovens and other similar applications.

### FEATURES

- Ø Temperature range 0°C to 280°C
- Ø Outstanding anti-wear performance
- Ø Long wet film life at high temperatures provides long term lubrication
- Ø Miscible with most ester based fluids

### DIRECTIONS FOR USE

- Ø ROCOL CHAIN GUARD 280 has been designed for application by automatic lubricators and should be used in accordance with the lubricator manufacturer's instructions
- Ø It can also be applied directly to the chain by brush or oilcan if desired

### Technical and Safety Data Sheets are available from:

**Fax Back Facility** : +44 (0)113 232 2770  
**Web Site** : [www.rocol.com](http://www.rocol.com)  
**Customer Service** : +44 (0)113 232 2700

Issue 22235e: Jan-04

1

#### **ROCOL Lubricants**

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

[www.rocol.com](http://www.rocol.com)

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.



# CHAIN GUARD 280

## TECHNICAL DATA (typical values)

Appearance	Pale yellow liquid
Base type	Synthetic ester
Temperature range	0°C to 280°C
Flash point	>300°C
Pour point	-33°C
Base fluid viscosity at 40°C	130cSt
Base fluid viscosity at 100°C	21 cSt
Evaporation loss at 200°C	1% in 6 hours
Storage	Storage temperature should be controlled to between 1 and 40 °C.
Pack sizes	5L, 20L

Issue 22235e: Jan-04

2

### ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

[www.rocol.com](http://www.rocol.com)

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

TECHNICAL DATA