



CHAIN GUARD HI LOAD SPRAY

High performance EP chain and conveyor lubricant with MoS₂.
Designed to effectively displace water, penetrate, lubricate and protect
against corrosion, particularly in wet and aggressive conditions.

FEATURES

- Ø Temperature range –30°C to 180°C
- Ø Outstanding EP performance (250kg weld load)
- Ø Excellent penetration
- Ø Tenacious water repellent film
- Ø Excellent corrosion protection
- Ø Applied film has good adhesion, reducing dripping or throw off

DIRECTIONS FOR USE

- Ø Shake well
- Ø Hold can upright and spray from a distance of approximately 25cm (10 inches) covering the chain thoroughly

Technical and Safety Data Sheets are available from:

Fax Back Facility : +44 (0)113 232 2770
Web Site : www.rocol.com
Customer Service : +44 (0)113 232 2700

Issue 22141d: Jan-04

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers.
There are many factors outside our control or knowledge which affect the use and performance
of our products, for which reason it is given without responsibility.



CHAIN GUARD HI LOAD SPRAY

TECHNICAL DATA (typical values)

Appearance	Grey liquid
Base type	Mineral oil
Solvent	Hydrocarbon
Propellant	CO ₂ (Carbon dioxide)
Temperature range	-30 ⁰ C to 180 ⁰ C
Base fluid viscosity at 40 ⁰ C	18cSt
Base fluid viscosity at 100 ⁰ C	5cSt
Shell 4 ball (IP 239)(ASTM D2596)	
Weld load	250 kg
Corrosion test (ASTM B 368)	
5% Salt Spray 200 hrs at 35 ⁰ C	0% (no corrosion)
Storage	Storage area should be: out of direct sunlight. Storage temperature should be kept below 50 °C.
Pack sizes	300 ml

Issue 22141d: Jan-04

2

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

TECHNICAL DATA