



FOODLUBE UNIVERSAL UNILUBE

**Food grade multipurpose EP grease fortified with PTFE.
Non-toxic lubricant designed for the automatic lubrication and
protection of ball, roller and plain bearings operating in food/clean
environments.**

FEATURES

- Ø Grease temperature range -50°C to 160°C
- Ø Outstanding EP performance (620 weld load)
- Ø Highly resistant to water wash off
- Ø Suitable for use in electrical motors and fans
- Ø Excellent corrosion protection
- Ø GS (geprüfte sicherheit) certified for tested safety
- Ø Does not contain: mineral hydrocarbons, animal derived materials, nut oils or genetically modified ingredients.
- Ø FDA Group 21 CFR 178.3570
- Ø NSF H1 registered – 121603
- Ø DIN V 10517

DIRECTIONS FOR USE

- Ø Prime the mounting point with Foodlube Universal before installing.
- Ø Select plug colour required and screw fully home until eyelet breaks off.
- Ø Screw unit onto a $\frac{1}{4}$ " BSP female mounting point.

Technical and Safety Data Sheets are available from:

Fax Back Facility : +44 (0)113 232 2770
Web Site : www.rocol.com
Customer Service : +44 (0)113 232 2700

Issue 15910b: Jan-04

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

TECHNICAL DATA



FOODLUBE UNIVERSAL UNILUBE

TECHNICAL DATA (typical values)

Yellow plug	1 month setting
Green plug	3 month setting
Red plug	6 month setting
Grey plug	12 month setting
Mounting thread size on Unilube	1/4" BSP male
Maximum pressure build up	4 bar
<u>GREASE DETAILS</u>	
Appearance	White, tenacious grease
NLGI No. (IP 50)(ASTM D217)	NLGI No. 2
Base type	Polyalphaolefin
Thickener	Aluminium complex soap
Solids	HLWS/PTFE
Temperature range	-50°C to 160°C
(Temperature range of unit)	0°C to 40°C
Drop point	>230°C
Base fluid viscosity at 40°C	47 cSt
Shell 4 ball (IP 239)(ASTM D2596)	
Weld load	620 kg
Copper corrosion test (IP 112)(ASTM D130)	Pass
Water washout test (IP 215)(ASTM D 1264)	<2.0%
Storage	Storage temperature should be controlled to between 1 and 40 °C.
Pack sizes	100 ml

Issue 15910b: Jan-04

2

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

TECHNICAL DATA