



GASSEAL

**Non Setting pipe sealant for metallic threaded joints
Primarily for Liquefied Petroleum Gases (LPG), Natural Gas, Air & Water**

FEATURES

- Ø Temperature range: -20°C to 125°C
- Ø Suitable for low pressure 2.9 psi (0.2 bar) L.P.G. and natural gas
- Ø Independently tested by BSI to BS EN 751-2 : 1997 Part 2 Class B for use with gas appliances and their auxiliary equipment
- Ø Joints can be assembled and pressure tested immediately
- Ø Non corrosive to aluminium, brass, copper, low carbon steel & zinc
- Ø Resists vibration
- Ø Compatible with foam forming leak testers
- Ø Suitable for use by *CORGI* registered gas installers
- Ø NOT SUITABLE FOR HIGH PRESSURE STORAGE INSTALLATIONS OR LPG IN LIQUID FORM

DIRECTIONS FOR USE

- Ø Do not apply in sub-zero temperatures
- Ø Use on gas appliances and their auxiliary equipment only
- Ø Not to be used on installation pipework
- Ø Ensure surfaces are clean and free of contaminants. Apply with a brush
- Ø The joints may be assembled and used immediately

Technical and Safety Data Sheets are available from:

Fax Back Facility : +44 (0)113 232 2770
Web Site : www.rocol.com
Customer Service : +44 (0)113 232 2700

Issue 28042b: Jan-04

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.



TECHNICAL DATA (typical values)

Appearance	Off-white compound
Unworked penetration (IP50)	275 – 295
Base type	Castor oil
Solids	Inorganic thickener
Specifications	BS EN 751-2 : 1997 Part 2 Class B
BSI test parameters:	
Operating temperature range	-20 ⁰ C to 125 ⁰ C
Test pressure	0.2 bar (2.9 psi)
Suitable applications	LPG & Natural gas (gas appliances and their auxiliary equipment only) Air Water Steam
Storage	Storage temperature should be controlled to between 1 and 40 °C.
Pack Sizes	300g

T
E
C
H
N
I
C
A
L

D
A
T
A

Issue 28042b: Jan-04

2

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.