M23660 GAS TAP LUBRICANT

Effective lubrication and sealing of gas taps and taper plug cocks. Developed in conjunction with cooker and tap manufacturers for the lubrication of taper gas taps operating with 1st, 2nd and 3rd family gases. Its use enables compliance with British Standard 5494, 1978, service No.6 (30,000 operations).
ROCOL M23660 Gas Tap Lubricant has been used by British Gas PLC for over 30 years, and demonstrated to be acceptable for continuous use at 120°C in a wide range of gas equipment applications including gas taps, cocks etc…

FEATURES

- Suitable for high temperature applications up to 120°C
- Good lubricating and sealing properties
- Excellent anti-wear and anti-seize properties

DIRECTIONS FOR USE

- ROCOL M23660 Gas Tap Lubricant can be applied manually or by a suitable applicator capable of handling an NLGI No.2 grease.
- For best results equipment should be cleaned or purged of previous lubricant prior to application of ROCOL M23660.

Technical and Safety Data Sheets are available from:

Fax Back Facility	:	+44 (0)113 232 2770
Web Site	:	www.rocol.com
Customer Service	:	+44 (0)113 232 2700

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760
www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.
ROCOL is a trade mark of ITW Inc.
The information in this publication is based on our experience and reports from customers.
There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

TECHNICAL DATA

M23660 GAS TAP LUBRICANT

TECHNICAL DATA (typical values)

Appearance	Smooth, blue-black grease
NLGI No. (IP 50)(ASTM D217)	NLGI No. 1/2
Base type	Severely refined mineral oil
Thickener	Organically modified clay
Solids	Molybdenum disulphide
Operating temperature (continuous)	up to 200^{0}C
Drop point (IP132)	Non-melting
Storage	Storage temperature should be controlled to between 1 and 40 °C.
Pack sizes	50g

TECHNICAL DATA

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.
ROCOL is a trade mark of ITW Inc.
The information in this publication is based on our experience and reports from customers.
There are many factors outside our control or knowledge which affect the use and performance
of our products, for which reason it is given without responsibility.