



PENETRATING SPRAY

Powerful penetrating fluid, with molybdenum disulphide, in an aerosol. A powerful jet application of lubricant that penetrates to give quick and effective release of corroded threaded fasteners or similar seized components. It contains molybdenum disulphide, to aid disassembly, and corrosion inhibitors to provide a protective film against further corrosive attack.

FEATURES

- Ø Excellent penetration of rust, scale, grease, oil etc...
- Ø Molybdenum disulphide aids dismantling
- Ø Protective film provides short term corrosion protection
- Ø Fast acting performance

DIRECTIONS FOR USE

- Ø Ideally remove any excessive oil, grease or dirt contamination.
- Ø Shake can, and coat thoroughly from approx 10-30 cm (4-12 inches)
- Ø In severe cases a second coating a few mins later may prove beneficial
- Ø Allow time for penetration to occur before attempting to release
- Ø Test compatibility with painted or coated surfaces and rubbers prior to application.

Technical and Safety Data Sheets are available from:

Fax Back Facility : +44 (0)113 232 2770
Web Site : www.rocol.com
Customer Service : +44 (0)113 232 2700

Issue 14021c: Jan-04

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

