

REFRIGERATION COMPRESSOR OIL

High quality oil for reciprocating, and screw, refrigeration compressors.

Designed to operate at extremely low temperatures whilst minimising the build up of varnish, sludge and waxy deposits.

FEATURES

- Ø Extremely low pour point (-45°C)
- Ø High thermal stability
- Ø Low volatility -long service life
- Ø Suitable for ammonia and all commonly used CFC refrigerants
- Ø Good compatibility with materials used in refrigeration systems
- Ø Extremely low waxing
- Ø Highly resistant to carbonisation

DIRECTIONS FOR USE

- Ø Compressor systems should be flushed and drained prior to filling with ROCOL Refrigeration Compressor Oil.
- Ø Although ROCOL Refrigeration Compressor Oil is compatible with other mineral oil based products the performance will be impaired if mixed.

Technical and Safety Data Sheets are available from:

Fax Back Facility : +44 (0)113 232 2770

Web Site : www.rocol.com

Customer Service : +44 (0)113 232 2700

Issue 31009b: Jan-04

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

WWW.rocol.com

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers.

There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.



REFRIGERATION COMPRESSOR OIL

TECHNICAL DATA (typical values)

Appearance	Clear amber liquid
Base type	Semi-synthetic
2 (1)	
Base fluid viscosity at 40°C	55 cSt
Dour point	-45°C
Pour point	-45 C
Storage	Storage temperature should be
Ciorago	controlled to between 1 and 40°C
Pack sizes	200 ltr, 1000 ltr

Issue 31009b: Jan-04 2

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com