



TUFLUBE ALLWEATHER

Water resistant adhesive lubricant for a wide range of applications. Versatile, extremely adhesive, self-repairing lubricant. For slides, plain bearings, & open gears particularly in high load and/or wet conditions.

FEATURES

- Ø Temperature range -30°C to 70°C
- Ø Outstanding EP performance (800kg weld load)
- Ø Excellent water displacing properties – can be applied to wet surfaces
- Ø Good corrosion protection
- Ø Highly resistant to water wash off
- Ø Tenacious, self-repairing film
- Ø Free from bitumen and solvents

DIRECTIONS FOR USE

- Ø Apply manually or with an applicator suitable for an NLGI No.1 grease
- Ø Do not mix with other lubricants as performance may be impaired

Technical and Safety Data Sheets are available from:

Fax Back Facility : +44 (0)113 232 2770
Web Site : www.rocol.com
Customer Service : +44 (0)113 232 2700

Issue 18271d: Jan-04

1

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

TECHNICAL DATA



TUFLUBE ALLWEATHER

TECHNICAL DATA (typical values)

Appearance	Smooth, black grease
Base oil	Highly refined mineral oil
Base oil viscosity at 40 ⁰ C	780 cSt
at 100 ⁰ C	42 cSt
Thickener	Aluminium soap
Solids	Graphite
NLGI number	0/1
Temperature range	-30 ⁰ C to 70 ⁰ C
Shell 4 ball (IP 239)	
Weld load	800 kg
Wear load index	107
Timken OK load	45 lbs
Corrosion resistance (ASTM B-117)	No corrosion (10 days)
Water spray off (ASTM D404)	<0.5% loss
Storage	Storage temperature should be controlled to between 1 and 40 °C.
Pack sizes	400gm, 5kg, 18kg

Issue 18271d: Jan-04

2

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

TECHNICAL DATA