



WIRE ROPE DRESSING

High performance, semi-fluid wire rope lubricant.
Semi-fluid grease containing a unique combination of lubricating solids. It is totally water repellent, cannot emulsify in water and, due to its non-tacky nature, will prevent build up of dust and contaminants on the rope. **ROCOL WIRE ROPE DRESSING** is used successfully on hoists, drag lines, cranes and ships, particularly in areas where salt water, dust, sand, effluent or other hostile conditions prevail.

FEATURES

- Ø Temperature range -30°C to 100°C
- Ø Excellent internal & external wear protection
- Ø Excellent internal & external corrosion protection
- Ø Withstands extreme wet /corrosive conditions
- Ø High performance - ensures extended relubrication intervals
- Ø Thin film keeps ropes clean from dust and dirt and are cleaner to handle
- Ø Does not drip or fling off
- Ø Also suitable as a gearbox grease for slow moving, highly loaded boxes

DIRECTIONS FOR USE

- Ø Application can be made by using a brush or swab
- Ø Minimum application temperature 0°C
- Ø For best results apply to clean, dry ropes

Technical and Safety Data Sheets are available from:

Fax Back Facility : +44 (0)113 232 2770
Web Site : www.rocol.com
Customer Service : +44 (0)113 232 2700

Issue 20026f: Jan-04

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.



WIRE ROPE DRESSING

TECHNICAL DATA (typical values)

Appearance	Soft, grey/black, tenacious grease
NLGI No. (IP 50)(ASTM D217)	NLGI No. 00
Base type	Severely refined mineral oil
Thickener	Organically modified clay
Solids	Blend of high load solids
Solvents	None
Temperature range	-30°C to 100°C
Minimum application temperature	0°C
Base fluid viscosity at 40°C	465 cSt
Approximate coverage - 25mm dia. (1") wire rope	approx. 50m per kg
Storage	Storage temperature should be controlled to between 1 and 40 °C.
Pack sizes	4kg, 18kg

Issue 20026f: Jan-04

2

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

TECHNICAL DATA