



WIRE ROPE SPRAY

High performance, de-watering wire rope lubricant in aerosol form. De-watering wire rope spray that can be applied even in wet conditions. it contains a petroleum solvent ensuring rapid penetration. ROCOL WIRE ROPE SPRAY is used successfully on hoists, drag lines, cranes and ships in areas where salt water, effluent or hostile weather conditions prevail.

FEATURES

- Ø Temperature range -30°C to 100°C
- Ø Excellent internal & external wear protection
- Ø Excellent internal & external corrosion protection
- Ø De-watering - can be applied to wet ropes
- Ø Withstands extreme wet /corrosive conditions
- Ø High performance - ensures extended relubrication intervals
- Ø Thin film keeps ropes clean from dust and dirt and are cleaner to handle

DIRECTIONS FOR USE

- Ø Shake can well before use
- Ø Hold upright and spray from a convenient distance
- Ø Apply a complete film over the rope surface
- Ø For best results apply to clean, dry ropes

Technical and Safety Data Sheets are available from:

Fax Back Facility : +44 (0)113 232 2770
Web Site : www.rocol.com
Customer Service : +44 (0)113 232 2700

Issue 20015d: Jan-04

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.



WIRE ROPE SPRAY

TECHNICAL DATA (typical values)

Appearance	Grey/green fluid
Base type	Severely refined mineral oil
Thickener	Organically modified clay
Solids	Blend of high load solids
Solvents	Hydrocarbon
Propellant	LPG (Hydrocarbon)
Temperature range	-30 ⁰ C to 100 ⁰ C
Base fluid viscosity at 40 ⁰ C	465 cSt
Approximate coverage	
25mm dia (1") wire rope	Approx 20 - 30 m per aerosol
Storage	Storage temperature should be kept below 50 °C. Storage area should be: out of direct sunlight.
Pack sizes	400ml

Issue 20015d: Jan-04

2

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

TECHNICAL DATA