



## Z25

**Light/medium duty, oily, multipurpose lubricant.  
Lubricating, penetrating and water displacing lubricant with good  
corrosion protection. Ideal for lubricating chains, hinges, linkages etc.**

### FEATURES

- Ø Temperature range –20°C to 110°C
- Ø Provides a thin, high performance, oily film
- Ø Good dewatering properties
- Ø Excellent penetration
- Ø Excellent corrosion protection indoors for up to 1 year
- Ø Specially formulated to clean oil contaminated parts
- Ø Ideal light lubrication of chains, hinges, linkages and pins
- Ø Does not contain silicones or chlorinated solvents

### DIRECTIONS FOR USE

- Ø Brush, dip or spray as required.

### Technical and Safety Data Sheets are available from:

**Fax Back Facility** : +44 (0)113 232 2770  
**Web Site** : [www.rocol.com](http://www.rocol.com)  
**Customer Service** : +44 (0)113 232 2700

**Issue 37018c: Jan-04**

1

#### **ROCOL Lubricants**

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

[www.rocol.com](http://www.rocol.com)

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers.  
There are many factors outside our control or knowledge which affect the use and performance  
of our products, for which reason it is given without responsibility.

TECHNICAL DATA



## Z25

### TECHNICAL DATA (typical values)

Bulk fluid appearance	Light brown oily fluid
Applied film appearance	Thin, oily film
Film thickness	Approximately 5-7 microns
Odour	Cherry
Base type	Highly refined Mineral oil
Solvent	Hydrocarbon solvent
Viscosity at 40 <sup>o</sup> C	4.0 cSt
Temperature range	-20 <sup>o</sup> C to 110 <sup>o</sup> C
Protection period	Indoors up to 1 year
Storage	Storage temperature should be kept below 50 °C. Storage area should be: out of direct sunlight.
Pack sizes	20L, 200L

Issue 37018c: Jan-04

2

#### ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

[www.rocol.com](http://www.rocol.com)

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

TECHNICAL DATA