



Z30

**Waxy film for long term outdoor corrosion protection.
Ideal for long term protection of machinery, elevators, forklift trucks,
underground installations, offshore platforms etc.**

FEATURES

- Ø Temperature range -20°C to 110°C
- Ø Heavy duty, waxy film for long term corrosion protection
- Ø Excellent corrosion protection outdoors for up to 2 year
- Ø Good dewatering properties
- Ø Good penetration
- Ø Can provide a light lubricating film in some applications
- Ø Ideal for outdoor corrosion protection of exposed metal parts
- Ø Does not contain silicones or chlorinated solvents

DIRECTIONS FOR USE

- Ø Brush, dip or spray as required.
- Ø Ensure a complete and thorough coating for maximum protection

Technical and Safety Data Sheets are available from:

Fax Back Facility : +44 (0)113 232 2770
Web Site : www.rocol.com
Customer Service : +44 (0)113 232 2700

Issue 34014f: Jan-04

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers.
There are many factors outside our control or knowledge which affect the use and performance
of our products, for which reason it is given without responsibility.



Z30

TECHNICAL DATA (typical values)

Bulk fluid appearance	Brown waxy fluid
Applied film appearance	Soft brown waxy film
Film thickness	Approximately 40-50 microns
Odour	Cherry/Almond
Base type	Paraffinic wax
Solvent	Hydrocarbon solvent
Propellant (Z30 SPRAY ONLY)	Carbon dioxide
Temperature range	-20°C to 110°C
Protection period	Outdoors up to 2 years
Salt spray test (ASTM B117)	
480 hours at 35°C	0% corrosion
Storage	Storage temperature should be kept below 50 °C. Storage area should be: out of direct sunlight.
Pack sizes	300ml aerosol, 5L, 20L, 200L

Issue 34014f: Jan-04

2

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

TECHNICAL DATA