



Z5

**Light duty, greaseless, multipurpose lubricant.
Water displacing, lubricating, penetrating and cleaning lubricant with
good corrosion protection. Ideal for drying out electrical components.**

FEATURES

- Ø Temperature range -20°C to 110°C
- Ø Ideal for light lubrication
- Ø Good dewatering properties
- Ø Excellent penetration
- Ø Excellent corrosion protection
- Ø Specially formulated to clean oil contaminated parts
- Ø Ideal for drying out electrical components and devices
- Ø Does not contain silicones or chlorinated solvents

DIRECTIONS FOR USE

- Ø Brush, dip or spray as required.

Technical and Safety Data Sheets are available from:

Fax Back Facility : +44 (0)113 232 2770
Web Site : www.rocol.com
Customer Service : +44 (0)113 232 2700

Issue 37008c: Jan-04

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers.
There are many factors outside our control or knowledge which affect the use and performance
of our products, for which reason it is given without responsibility.

T
E
C
H
N
I
C
A
L

D
A
T
A

