



FOLIAC SUPER RED P.J.C.

**Setting pipe sealant for metallic threaded and flanged joints
Primarily for Petrol, Diesel, Fuel oils, Mineral oils, Gases, Air & Water**

FEATURES

- Ø Temperature range -20°C to 250°C
- Ø Suitable for pressures up to 150 psi (10 bar)
- Ø Pressure test after a minimum 24 hours
- Ø Sets hard but flexible
- Ø Resists vibration and thermal expansion

DIRECTIONS FOR USE

- Ø Do not apply at sub-zero temperatures
- Ø Stir well before use
- Ø Ensure surfaces are clean and free of contaminants. Apply with a brush
- Ø Assemble between 10-20 minutes
- Ø Pressure test after a minimum of 24 hours at ambient ($20-25^{\circ}\text{C}$)
- Ø Lower temperatures will extend drying time

Technical and Safety Data Sheets are available from:

Fax Back Facility : +44 (0)113 232 2770
Web Site : www.rocol.com
Customer Service : +44 (0)113 232 2700

Issue 3005a: 16/04/02

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

www.rocolshop.com

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers.
There are many factors outside our control or knowledge which affect the use and performance
of our products, for which reason it is given without responsibility.



FOLIAC SUPER RED P.J.C.

TECHNICAL DATA (typical values)

Appearance	Dark red viscous liquid
Viscosity (Brookfield) @25°C	5000 cps
Base type	Organic resin & solvents
Solids	Iron Oxide
Temperature range	-20°C to 250°C
Pressure	Up to 150 psi (10 bar)
Suitable applications	Petrol Diesel Fuel oils Mineral oils Paraffin & White spirit Alcohol LPG & Natural gas Air Water
Storage	Store away from sources of heat or ignition. Storage area should be well ventilated under cover. Storage and transfer equipment should be adequately earthed and bonded to prevent the accumulation of static charges.
Pack sizes	375g

Issue 3005a: 16/04/02

2

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

www.rocolshop.com

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

TECHNICAL DATA